

# SPINDLE SHAPERS



# R-12QC DIGI-SET ACCU-SHAPER



## Standard Features: R12QC

- 10 HP Spindle Drive Motor, TEFC
- HSK F 63 Spindle Nose
- (3) Quick Change Spindles, 1-1/4" Dia. 3" Long
- (2) Loaded Spindle Cradles
- Safety Interlock Push Button Tool Change
- 6" Vertical Spindle Travel Range
- Front Mounted Cutter Head Load Meter
- Inverter Drive Spindle Speed Control
- 4-spindle Speeds, 6,000, 8,000, 10,000 & 12,000 RPM
- Digital Spindle RPM Display On Inverter
- Rotary Drum Speed Selector Switch
- Reversing Spindle Switch
- Electronic Spindle Brake
- Safety Interlock Carriage Access Door
- Precision Linear Bearing Carriage Guides
- 1-1/2" Diameter Lead Screw Spindle Adjustment
- Digital Display Spindle Height Positioning
- Powered Spindle Raising And Lowering
- 48" X 38" Table Area
- 3/4" Wide Table Slot
- 8" Maximum Table Throat Diameter
- 7-3/4" Cutter Diameter Below Table
- 10" Cutter Diameter Above Table
- (2) Table Insert Rings
- 37" Work Table Height
- Independent Micro-adjusting Fences
- Digital Display Fence Position
- 5" X 21" Wood Fence Plates
- Independent Easy Access Dust Hood
- 4" Diameter Dust Hood Outlet
- 2-1/2" Below Table Dust Outlet
- Rear Safety Guard
- Lock Out/ Tag Out Disconnect Switch
- Wired 3-phase 230/460 Volt, 60 Hz
- Tapped Power Feeder Mounting
- Machine Weight: 1380 Lbs.

## Optional Features:

- Additional 1-1/4" Spindles
- 15 HP Spindle Drive Motor
- CNC Spindle and Fence Positioning

# R-11 8-SPEED HEAVY DUTY SHAPER

➔ **DESIGNED FOR  
MILLWORK  
PRODUCTION**



## Standard Features: R1175

- Quick Change Spindles, 1 ¼" and 1"
- #4 Morse Taper Spindle Nose
- 6" Usable Spindle Under Nut
- Complete Set of Spindle Spacers, ½" - 1"
- 6" Vertical Spindle Travel Range
- 7.5 HP Spindle Drive Motor, TEFC
- Front Mounted Load Meter
- Front Hinged Carriage Access Door
- Inverter Drive Spindle Speed Control
- 8 Spindle Speeds, 3600, 4200, 5000, 5400, 6000, 7000, 8000, 9000
- Rotary Drum Speed Selection Switch
- Reversing Spindle
- Electronic Spindle Brake
- Precision Linear Bearing Carriage Guides
- 1 ½" Diameter Lead Screw Spindle Adjustment
- Digital Display Spindle Height Positioning
- Oversized Hand Wheel Spindle Adjustment
- 48" x 38" Table Area
- ¾" Wide Table Slot
- 8" Maximum Throat Diameter
- 7 ¾" Maximum Cutter Diameter
- (2) Table Insert Rings
- Independent Micro-Adjusting Fences
- 4 Position Fence Offset Turrets
- 5" x 21" Wood Fence Plates
- Independent Dust Hood Housing
- 4" Dust Hood Outlet
- 4" Below Table Dust Outlet
- Tapped Power Feeder Mounting Holes
- 37" Work Table Height
- Rear Safety Belt Guard
- Lock Out/Tag Out Disconnect Switch
- Wired 3-Phase 230/460 Volt, 60 Hz
- Machine Weight: 1380 lbs.

## Optional Features:

- 10 HP Spindle Drive Motor (R1110)
- Additional 1 ¼" Spindle
- Additional 1" Spindle
- Digital Fence Setting Display

# R-10 SINGLE SPINDLE SHAPER

DESIGNED FOR CABINET SHOP PRODUCTION



## Standard Features:

- 1" or 1 1/4" Spindle (Specify)
- 5 H.P., 3-Phase 220/440 Volt Motor
- Magnetic Controls
- Spindle Speeds 10,000/8,000 RPM, V-belt Driven
- Electronic Reversing Switch
- Table Size 36" Wide x 30" Deep
- Slot in Table (3/4" Wide x 3/8" Deep)
- Fully Adjustable Fences
- Dust Hood, 6" x 7" Flange Opening
- Working Height 36"
- 6" Maximum Cutter Diameter
- 1/2", 3/4" and 1" Spindle Spacers
- Machine Weight 782 lbs.

## Optional Features:

- 3 HP, 1-Phase Motor
- 1" Diameter Spindle Cartridge
- 1 1/4" Diameter Spindle Cartridge
- 7.5 HP, 3-Phase Motor

DISTRIBUTED BY

**RITTER**  
MANUFACTURING, INC.

1300B West Fourth St. – Antioch, CA 94509  
(925) 757-7296 • Fax (925) 757-7083  
[www.rittermfg.com](http://www.rittermfg.com)